

DB 8820 - Duobond Pit Fill

Printing: 08/09/2026

Date of compilation: 27/08/2024

Version: 1

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1 Product identifier:** DB 8820 - Duobond Pit Fill**Other means of identification:**

UFI: R8ES-W00F-000D-052S

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses (Professional users): Adhesive for glass

For Professional users only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

DB-Imagineering BV

Laarakkerweg 10

5061 JR Oisterwijk - Netherlands

Phone: 0135444440

info@db-img.com

www.duobond.com

Duobond is a brand name of DB-Imagineering BV

1.4 Emergency telephone number: Within the European Union: 112**SECTION 2: HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture:****CLP Regulation (EC) No 1272/2008:**

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Acute 1: Hazardous to the aquatic environment, acute hazard, Category 1, H400

Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard, Category 1, H410

Eye Irrit. 2: Eye irritation, Category 2, H319

Skin Irrit. 2: Skin irritation, Category 2, H315

Skin Sens. 1A: Sensitisation, skin, Category 1A, H317

STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

2.2 Label elements:**CLP Regulation (EC) No 1272/2008:****Warning****Hazard statements:**

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

STOT SE 3: H335 - May cause respiratory irritation.

Precautionary statements:

P264: Wash thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P302+P352: IF ON SKIN: Wash with plenty of water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Supplementary information:

Contains 2-hydroxyethyl acrylate.

- CONTINUED ON NEXT PAGE -

DB 8820 - Duobond Pit Fill

Printing: 08/09/2026

Date of compilation: 27/08/2024

Version: 1

SECTION 2: HAZARDS IDENTIFICATION (continued)

Substances that contribute to the classification

Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate; (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate

UFI: R8ES-W00F-000D-052S

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Not relevant

3.2 Mixture:**Chemical description:** Acrylic resin**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 5888-33-5 EC: 227-561-6 Index: 607-756-00-6 REACH: 01-2119957862-25-XXXX	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate ⁽¹⁾ Self-classified		25 - <50%
	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Skin Sens. 1A: H317 - Warning 	
CAS: 42978-66-5 EC: 256-032-2 Index: 607-249-00-X REACH: 01-2119484613-34-XXXX	(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate ⁽¹⁾ ATP CLP00		10 - <25%
	Regulation 1272/2008	Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335 - Warning 	
CAS: 7473-98-5 EC: 231-272-0 Index: Not relevant REACH: 01-2119472306-39-XXXX	2-hydroxy-2-methylpropiophenone ⁽¹⁾ Self-classified		5 - <10%
	Regulation 1272/2008	Acute Tox. 4: H302; Aquatic Chronic 3: H412 - Warning 	
CAS: 79-92-5 EC: 201-234-8 Index: Not relevant REACH: 01-2119446293-40-XXXX	Camphene ⁽¹⁾ Self-classified		<1%
	Regulation 1272/2008	Aquatic Chronic 1: H410; Eye Irrit. 2: H319; Flam. Sol. 2: H228 - Warning 	
CAS: 818-61-1 EC: 212-454-9 Index: 607-072-00-8 REACH: 01-2119459345-34-XXXX	2-hydroxyethyl acrylate ⁽¹⁾ Self-classified		<1%
	Regulation 1272/2008	Acute Tox. 3: H311; Acute Tox. 4: H302; Aquatic Acute 1: H400; Eye Dam. 1: H318; Skin Corr. 1B: H314; Skin Sens. 1: H317 - Danger 	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	Specific concentration limit
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate CAS: 42978-66-5 EC: 256-032-2	% (w/w) >=10: STOT SE 3 - H335
2-hydroxyethyl acrylate CAS: 818-61-1 EC: 212-454-9	% (w/w) >=0,2: Skin Sens. 1 - H317

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
2-hydroxy-2-methylpropiophenone CAS: 7473-98-5 EC: 231-272-0	LD50 oral	1694 mg/kg	Rat
	LD50 dermal	Not relevant	
	LC50 inhalation vapour	Not relevant	
2-hydroxyethyl acrylate CAS: 818-61-1 EC: 212-454-9	LD50 oral	500 mg/kg	
	LD50 dermal	300 mg/kg	
	LC50 inhalation vapour	Not relevant	

- CONTINUED ON NEXT PAGE -

DB 8820 - Duobond Pit Fill

Printing: 08/09/2026

Date of compilation: 27/08/2024

Version: 1

SECTION 4: FIRST AID MEASURES**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media:****Suitable extinguishing media:**

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EEC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

- CONTINUED ON NEXT PAGE -

DB 8820 - Duobond Pit Fill

Printing: 08/09/2026

Date of compilation: 27/08/2024

Version: 1

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

It is recommended to transfer at a slow speed to avoid the creation of electrostatic charges that could affect flammable products. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

- CONTINUED ON NEXT PAGE -

DB 8820 - Duobond Pit Fill

Printing: 08/09/2026

Date of compilation: 27/08/2024

Version: 1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no applicable occupational exposure limits for the substances contained in the product

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate CAS: 5888-33-5 EC: 227-561-6	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	1,39 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	4,9 mg/m ³	Not relevant
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate CAS: 42978-66-5 EC: 256-032-2	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	1,7 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	2,35 mg/m ³	Not relevant
2-hydroxy-2-methylpropiophenone CAS: 7473-98-5 EC: 231-272-0	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	1 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	3,5 mg/m ³	Not relevant
Camphene CAS: 79-92-5 EC: 201-234-8	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	1,25 mg/kg	Not relevant	0,21 mg/kg	Not relevant
	Inhalation	110,19 mg/m ³	Not relevant	110,19 mg/m ³	Not relevant
2-hydroxyethyl acrylate CAS: 818-61-1 EC: 212-454-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	Not relevant	2,4 mg/m ³

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate CAS: 5888-33-5 EC: 227-561-6	Oral	Not relevant	Not relevant	0,83 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	0,83 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	1,45 mg/m ³	Not relevant
2-hydroxy-2-methylpropiophenone CAS: 7473-98-5 EC: 231-272-0	Oral	Not relevant	Not relevant	0,4 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	0,5 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	0,9 mg/m ³	Not relevant
Camphene CAS: 79-92-5 EC: 201-234-8	Oral	0,625 mg/kg	Not relevant	0,1 mg/kg	Not relevant
	Dermal	0,625 mg/kg	Not relevant	0,1 mg/kg	Not relevant
	Inhalation	54,3 mg/m ³	Not relevant	54,3 mg/m ³	Not relevant
2-hydroxyethyl acrylate CAS: 818-61-1 EC: 212-454-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	Not relevant	1,2 mg/m ³

PNEC:

Identification					
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate CAS: 5888-33-5 EC: 227-561-6	STP	2 mg/L	Fresh water	0,001 mg/L	
	Soil	0,029 mg/kg	Marine water	0 mg/L	
	Intermittent	0,007 mg/L	Sediment (Fresh water)	0,145 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0,015 mg/kg	
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate CAS: 42978-66-5 EC: 256-032-2	STP	10 mg/L	Fresh water	0,005 mg/L	
	Soil	0,095 mg/kg	Marine water	0 mg/L	
	Intermittent	0,046 mg/L	Sediment (Fresh water)	0,487 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0,049 mg/kg	
2-hydroxy-2-methylpropiophenone CAS: 7473-98-5 EC: 231-272-0	STP	45 mg/L	Fresh water	0,002 mg/L	
	Soil	0,001 mg/kg	Marine water	0 mg/L	
	Intermittent	0,019 mg/L	Sediment (Fresh water)	0,009 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0,001 mg/kg	

- CONTINUED ON NEXT PAGE -

DB 8820 - Duobond Pit Fill

Printing: 08/09/2026

Date of compilation: 27/08/2024

Version: 1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Camphene CAS: 79-92-5 EC: 201-234-8	STP	10 mg/L	Fresh water	0,001 mg/L
	Soil	0,021 mg/kg	Marine water	0 mg/L
	Intermittent	0,001 mg/L	Sediment (Fresh water)	0,026 mg/kg
	Oral	0,00208 g/kg	Sediment (Marine water)	0,003 mg/kg
2-hydroxyethyl acrylate CAS: 818-61-1 EC: 212-454-9	STP	10 mg/L	Fresh water	0,017 mg/L
	Soil	0,003 mg/kg	Marine water	0,002 mg/L
	Intermittent	0,036 mg/L	Sediment (Fresh water)	0,064 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0,006 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: A)		EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Butyl, Breakthrough time: > 480 min, Thickness: 0.3 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN ISO 16321-1:2022 + EN ISO 16321-3:2022 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing			Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes		EN ISO 20347:2022/A1:2024	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2022 y EN 13832-1:2019

F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

- CONTINUED ON NEXT PAGE -

DB 8820 - Duobond Pit Fill

Printing: 08/09/2026

Date of compilation: 27/08/2024

Version: 1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	0 % weight
V.O.C. density at 20 °C:	0 kg/m ³ (0 g/L)
Average carbon number:	Not relevant
Average molecular weight:	Not relevant

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Fluid
Colour:	Colourless
Odour:	Mild
Odour threshold:	Not relevant *

Volatility:

Boiling point at atmospheric pressure:	270 °C
Vapour pressure at 20 °C:	79 Pa
Vapour pressure at 50 °C:	422,03 Pa (0,42 kPa)
Evaporation rate at 20 °C:	Not relevant *

Product description:

Density at 20 °C:	1049,2 kg/m ³
Relative density at 20 °C:	1,049
Dynamic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 40 °C:	Not relevant *
Concentration:	Not relevant *
pH:	ca. 6
Relative vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Not relevant *
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *

Flammability:

Flash Point:	Non Flammable (>60 °C)
--------------	------------------------

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

DB 8820 - Duobond Pit Fill

Printing: 08/09/2026

Date of compilation: 27/08/2024

Version: 1

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Flammability (solid, gas):	Not relevant *
Autoignition temperature:	214 °C
Lower flammability limit:	Not relevant *
Upper flammability limit:	Not relevant *
Particle characteristics:	
Median equivalent diameter:	Not relevant *

9.2 Other information:**Information with regard to physical hazard classes:**

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *
Corrosive to metals:	Not relevant *
Heat of combustion:	Not relevant *
Aerosols-total percentage (by mass) of flammable components:	Not relevant *

Other safety characteristics:

Surface tension at 20 °C:	Not relevant *
Refraction index:	Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Precaution	Not applicable	Precaution	Precaution	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:**

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- CONTINUED ON NEXT PAGE -

DB 8820 - Duobond Pit Fill

Printing: 08/09/2026

Date of compilation: 27/08/2024

Version: 1

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.

- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.

- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.

- Contact with the eyes: Causes serious eye irritation.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

IARC: Not relevant

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.

- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
2-hydroxy-2-methylpropiophenone CAS: 7473-98-5 EC: 231-272-0	LD50 oral	1694 mg/kg	Rat
	LD50 dermal		
	LC50 inhalation vapour		
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate CAS: 42978-66-5 EC: 256-032-2	LD50 oral	6800 mg/kg	Rat
	LD50 dermal		
	LC50 inhalation vapour	118 mg/L (4 h)	Rat
Camphene CAS: 79-92-5 EC: 201-234-8	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	8189 mg/kg	Rabbit
	LC50 inhalation dust		
2-hydroxyethyl acrylate CAS: 818-61-1 EC: 212-454-9	LD50 oral	500 mg/kg	
	LD50 dermal	300 mg/kg	Rabbit
	LC50 inhalation vapour		

11.2 Information on other hazards:

- CONTINUED ON NEXT PAGE -

DB 8820 - Duobond Pit Fill

Printing: 08/09/2026

Date of compilation: 27/08/2024

Version: 1

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Not relevant

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Very toxic to aquatic life with long lasting effects.

12.1 Toxicity:**Acute toxicity:**

Identification	Concentration	Species	Genus
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate CAS: 5888-33-5 EC: 227-561-6	LC50	>0.1 - 1 mg/L (96 h)	Fish
	EC50	>0.1 - 1 mg/L (48 h)	Crustacean
	EC50	>0.1 - 1 mg/L (72 h)	Algae
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate CAS: 42978-66-5 EC: 256-032-2	LC50	5,5 mg/L (96 h)	Leuciscus idus
	EC50	88,7 mg/L (48 h)	Daphnia magna
	EC50	28 mg/L (72 h)	Scenedesmus subspicatus
2-hydroxy-2-methylpropiophenone CAS: 7473-98-5 EC: 231-272-0	LC50	>10 - 100 mg/L (96 h)	Fish
	EC50	>10 - 100 mg/L (48 h)	Crustacean
	EC50	>10 - 100 mg/L (72 h)	Algae
Camphene CAS: 79-92-5 EC: 201-234-8	LC50	0,72 mg/L (96 h)	Brachydanio rerio
	EC50	46 mg/L (24 h)	Daphnia magna
	EC50	Not relevant	
2-hydroxyethyl acrylate CAS: 818-61-1 EC: 212-454-9	LC50	4,7 mg/L (96 h)	Pimephales promelas
	EC50	0,78 mg/L (48 h)	Daphnia magna
	EC50	Not relevant	

Chronic toxicity:

Identification	Concentration	Species	Genus
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate CAS: 5888-33-5 EC: 227-561-6	NOEC	Not relevant	
	NOEC	0,092 mg/L	Daphnia magna
2-hydroxyethyl acrylate CAS: 818-61-1 EC: 212-454-9	NOEC	Not relevant	
	NOEC	1,8 mg/L	Daphnia magna

12.2 Persistence and degradability:**Substance-specific information:**

Identification	Degradability		Biodegradability	
Camphene CAS: 79-92-5 EC: 201-234-8	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	4 %
2-hydroxyethyl acrylate CAS: 818-61-1 EC: 212-454-9	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	78 %

12.3 Bioaccumulative potential:**Substance-specific information:**

Identification	Bioaccumulation potential	
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate CAS: 42978-66-5 EC: 256-032-2	BCF	
	Pow Log	2,77
	Potential	

- CONTINUED ON NEXT PAGE -

DB 8820 - Duobond Pit Fill

Printing: 08/09/2026

Date of compilation: 27/08/2024

Version: 1

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Bioaccumulation potential	
Camphene	BCF	1290
CAS: 79-92-5	Pow Log	4.22
EC: 201-234-8	Potential	Very High
2-hydroxyethyl acrylate	BCF	0.41
CAS: 818-61-1	Pow Log	-0.21
EC: 212-454-9	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Camphene	Koc	Not relevant	Henry	Not relevant
CAS: 79-92-5	Conclusion	Not relevant	Dry soil	Not relevant
EC: 201-234-8	Surface tension	1,098E-2 N/m (205,93 °C)	Moist soil	Not relevant
2-hydroxyethyl acrylate	Koc	Not relevant	Henry	Not relevant
CAS: 818-61-1	Conclusion	Not relevant	Dry soil	Not relevant
EC: 212-454-9	Surface tension	2,487E-2 N/m (25 °C)	Moist soil	Not relevant

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Hazardous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2025 and RID 2025:

- CONTINUED ON NEXT PAGE -

DB 8820 - Duobond Pit Fill

Printing: 08/09/2026

Date of compilation: 27/08/2024

Version: 1

SECTION 14: TRANSPORT INFORMATION (continued)

- 14.1 UN number or ID number:** UN3082
- 14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate)
- 14.3 Transport hazard class(es):** 9
- Labels:** 9
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**
- Special regulations: 274, 335, 375, 601, 650
- Tunnel restriction code: -
- Physico-Chemical properties: see section 9
- Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 42-24:



- 14.1 UN number or ID number:** UN3082
- 14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate)
- 14.3 Transport hazard class(es):** 9
- Labels:** 9
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** Yes
- 14.6 Special precautions for user**
- Special regulations: 375, 335, 274, 969
- EmS Codes: F-A, S-F
- Physico-Chemical properties: see section 9
- Limited quantities: 5 L
- Segregation group: Not relevant
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

Transport of dangerous goods by air:

With regard to IATA/ICAO 2026:



- 14.1 UN number or ID number:** UN3082
- 14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate)
- 14.3 Transport hazard class(es):** 9
- Labels:** 9
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**
- Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

SECTION 15: REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

- CONTINUED ON NEXT PAGE -

DB 8820 - Duobond Pit Fill

Printing: 08/09/2026

Date of compilation: 27/08/2024

Version: 1

SECTION 15: REGULATORY INFORMATION (continued)

- Article 95, REGULATION (EU) No 528/2012: Not relevant
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EU) 2019/1021 on persistent organic pollutants: Not relevant
- Regulation (EU) No 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
E1	ENVIRONMENTAL HAZARDS	100,000	200,000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION**Legislation related to safety data sheets:**

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Not relevant

Texts of the legislative phrases mentioned in section 2:

- H400: Very toxic to aquatic life.
- H410: Very toxic to aquatic life with long lasting effects.
- H317: May cause an allergic skin reaction.
- H315: Causes skin irritation.
- H335: May cause respiratory irritation.
- H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

- Acute Tox. 3: H311 - Toxic in contact with skin.
- Acute Tox. 4: H302 - Harmful if swallowed.
- Aquatic Acute 1: H400 - Very toxic to aquatic life.
- Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
- Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
- Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
- Eye Dam. 1: H318 - Causes serious eye damage.
- Eye Irrit. 2: H319 - Causes serious eye irritation.
- Flam. Sol. 2: H228 - Flammable solid.
- Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.
- Skin Irrit. 2: H315 - Causes skin irritation.
- Skin Sens. 1: H317 - May cause an allergic skin reaction.
- Skin Sens. 1A: H317 - May cause an allergic skin reaction.
- STOT SE 3: H335 - May cause respiratory irritation.

- CONTINUED ON NEXT PAGE -

DB 8820 - Duobond Pit Fill

Printing: 08/09/2026

Date of compilation: 27/08/2024

Version: 1

SECTION 16: OTHER INFORMATION (continued)**Classification procedure:**

Aquatic Acute 1: Calculation method
 Aquatic Chronic 1: Calculation method
 Skin Sens. 1A: Calculation method
 Skin Irrit. 2: Calculation method
 STOT SE 3: Calculation method
 Eye Irrit. 2: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
 IMDG: International maritime dangerous goods code
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organisation
 COD: Chemical Oxygen Demand
 BOD5: 5day biochemical oxygen demand
 BCF: Bioconcentration factor
 LD50: Lethal Dose 50
 LC50: Lethal Concentration 50
 EC50: Effective concentration 50
 LogPOW: Octanolwater partition coefficient
 Koc: Partition coefficient of organic carbon
 UFI: unique formula identifier
 IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -